

# Pietra

## Wood & Stone

### THE RADIANCE RANGE

Performance, with efficiency.

A selection of engineered floors, designed to provide maximum durability and efficiency, when used with under floor heating & cooling systems.

9+4 mm	Rustic Extra	Rustic A/B	Rustic A	1st Grade	Prime
220mm Wide					
200mm Wide					
180mm Wide					
160mm Wide					
140mm Wide					
120mm Wide					

#### GRADING SPECIFICATION

Prime. Maximum knot diameter 3 - 5mm. Limited colour variation.

1st Grade. Maximum knot diameter 15mm. Low colour variation.

Rustic A. Maximum knot diameter of 30mm. Medium colour variation

Rustic AB. Maximum knot diameter of 60mm. High colour variation.

Rustic Extra. Maximum knot diameter of 70mm. High colour variation with some open knots

#### TECHNICAL INFORMATION.

Thickness: 12mm & 13mm

Wear Layer: 4mm. A tolerance of +/- 0.5mm is allowed.

Board Lengths: 600 - 2950mm with 85% over 1800mm.

Construction: 4mm wear layer glued to 9mm plywood

Other Information: Bevelled edges to the two long sides only. Squared edge option also available. Tongue & grooved profile to all four sides.

# RADIANCE RANGE

A SMALL SELECTION OF THE COLOURS AVAILABLE





**RADIANCE RANGE**  
FOR MORE INFORMATION PLEASE CALL  
01225 783527 or Email [info@pwasltd.com](mailto:info@pwasltd.com)