

Pietra

Wood & Stone

THE RADIANCE RANGE

Performance, with efficiency.

A selection of engineered floors, designed to provide maximum durability and efficiency, when used with under floor heating & cooling systems.

9+4 mm	Rustic Extra	Rustic A/B	Rustic A	1st Grade	Prime
220mm Wide	✓	✓	✓	✓	✓
200mm Wide	✓	✓	✓	✓	✓
180mm Wide	✓	✓	✓	✓	✓
160mm Wide	✓	✓	✓	✓	✓
140mm Wide	✓	✓	✓	✓	✓
120mm Wide	✓	✓	✓	✓	✓

GRADING SPECIFICATION

Prime. Maximum knot diameter 3 - 5mm. Limited colour variation.

1st Grade. Maximum knot diameter 15mm. Low colour variation.

Rustic A. Maximum knot diameter of 30mm. Medium colour variation

Rustic AB. Maximum knot diameter of 60mm. High colour variation.

Rustic Extra. Maximum knot diameter of 70mm. High colour variation with some open knots

TECHNICAL INFORMATION.

Thickness: 12mm & 13mm

Wear Layer: 4mm. A tolerance of +/- 0.5mm is allowed.

Board Lengths: 600 - 2950mm with 85% over 1800mm.

Construction: 4mm wear layer glued to 9mm plywood

Other Information: Bevelled edges to the two long sides only. Squared edge option also available. Tongue & grooved profile to all four sides.

RADIANCE RANGE

A SMALL SELECTION OF THE COLOURS AVAILABLE





RADIANCE RANGE
FOR MORE INFORMATION PLEASE CALL
01225 783527 or Email info@pwasltd.com